

## VARIOUS MODELS FOR DIFFERENT POOL SIZES

For residential and semi-commercial pools

### Product Features

1. Three models to choose: 15, 25, 45g/hr
2. With or without built-in pump timer
3. Self cleaning reverse polarity
4. Quality titanium cells
5. With or without built-in lighting transformer
6. Maximum working pressure: 250kPa/36psi/2.5bar



## Characteristics

Salt chlorination is a method of sanitizing swimming pools with chlorine generated by electrolysis. The electrolysis is achieved by passing the saltwater solution through a weak electric charge in an electrolytic cell, which converts sodium chloride (salt) in the water into chlorine gas. The gas is dissolved in the water and becomes sodium hypochlorite (liquid chlorine).

Safe and environmentally friendly, salt water technology brings you:

Relaxation: Your pool is automatically disinfected

Safety: Significant reduction in the need to store and handle chlorine

- Health and well-being: Saltwater does not irritate the eyes and dries out skin

| Kodu Code | Tanım Description                        | Tuz Seviyesi Salt Level (ppm) | Hücre Çıkışı Cell Output (gram/h) | Fiberglas Fiberglass Pool (L) | Beton Concrete Pool (L) | Havuz ışığı Pool Light Voltage | Giriş Gerilimi Input Voltage /Freq | IP Derecelendirme IP Rating | Ağırlık Weight (kg) |
|-----------|--|-------------------------------|-----------------------------------|-------------------------------|-------------------------|--------------------------------|------------------------------------|-----------------------------|---------------------|
| RTL15-E   | Standard Version                         | 4000                          | 15                                | 50,000                        | 45,000                  | N/A                            | 240V<br>60/50Hz                    | IPX4                        | 6.5                 |
| RTL25-E   |  |                               | 25                                | 75,000                        | 70,000                  |                                |                                    |                             | 7.4                 |
| RTL50-E   |  |                               | 45                                | 120,000                       | 110,000                 |                                |                                    |                             | 9.7                 |
| RTL15-T   | With Time Clock                          | 4000                          | 15                                | 50,000                        | 45,000                  | N/A                            | 240V<br>60/50Hz                    | IPX4                        | 6.6                 |
| RTL25-T   |  |                               | 25                                | 75,000                        | 70,000                  |                                |                                    |                             | 7.5                 |
| RTL50-T   |  |                               | 45                                | 120,000                       | 110,000                 |                                |                                    |                             | 9.8                 |
| RTL15-TLT | With Time Clock & Pool Light Transformer | 4000                          | 15                                | 50,000                        | 45,000                  | 12V AC                         | 240V<br>60/50Hz                    | IPX4                        | 8.4                 |
| RTL25-TLT |  |                               | 25                                | 75,000                        | 70,000                  |                                |                                    |                             | 8.8                 |

## Installation Diagram

